



**jalas**<sup>®</sup> **green line**

## JALAS<sup>®</sup> 6428 PRIMA

EN ISO 20345:2011, S3 SRC

**PROPERTIES** Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

**PRIMARY ENVIRONMENTS OF USE** Outdoors, metal-free requirements for shoes, environments with risk for outsole penetration

**FEATURES** Oil-resistant outsole, metal free, anti-static properties, ventilating insole, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

**UPPER MATERIAL** Full-grain leather

**SOLE MATERIAL** Plastic shank, PU outsole

**INSOLE** FX2 Pro

**FITTING** Narrow/Regular  
**SIZE RANGE (EU)** 36-47

CE



Composite toecap



Ergothan Shock Absorption System



Nail protection in plasma-treated composite (PTC) textile



Anti-static properties



Water repellent



ESD



Oil-resistant outsole



**jalas**<sup>®</sup> **green line**

## JALAS<sup>®</sup> 6428 PRIMA

EN ISO 20345:2011, S3 SRC

**PROPERTIES** Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

**PRIMARY ENVIRONMENTS OF USE** Outdoors, metal-free requirements for shoes, environments with risk for outsole penetration

**FEATURES** Oil-resistant outsole, metal free, anti-static properties, ventilating insole, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

**UPPER MATERIAL** Full-grain leather

**SOLE MATERIAL** Plastic shank, PU outsole

**INSOLE** FX2 Pro

**FITTING** Narrow/Regular  
**SIZE RANGE (EU)** 36-47

CE



Composite toecap



Ergothan Shock Absorption System



Nail protection in plasma-treated composite (PTC) textile



Anti-static properties



Water repellent



ESD



Oil-resistant outsole