



jalas[®] **green line**

JALAS[®] 6438 TEMPERA

EN ISO 20345:2011, S3 SRC

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, extremely warm, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors, metal-free requirements for shoes, environments with risk for outsole penetration, cold environments, harsh environments

FEATURES ProNose toe reinforcement, oil-resistant outsole, metal free, anti-static properties, pull loops, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL PU-coated leather, split leather

SOLE MATERIAL Plastic shank, PU outsole

INSOLE FX2 Supreme

FITTING Narrow/Regular

SIZE RANGE (EU) 36-47

CE



Composite toecap



Ergo-Shock Absorption System



Nail protection in plasma-treated composite (PTC) textile



Winter model



Water repellent



Anti-static properties



Oil-resistant outsole



ESD



ProNose toe reinforcement



jalas[®] **green line**

JALAS[®] 6438 TEMPERA

EN ISO 20345:2011, S3 SRC

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, extremely warm, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors, metal-free requirements for shoes, environments with risk for outsole penetration, cold environments, harsh environments

FEATURES ProNose toe reinforcement, oil-resistant outsole, metal free, anti-static properties, pull loops, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL PU-coated leather, split leather

SOLE MATERIAL Plastic shank, PU outsole

INSOLE FX2 Supreme

FITTING Narrow/Regular

SIZE RANGE (EU) 36-47

CE



Composite toecap



Ergo-Shock Absorption System



Nail protection in plasma-treated composite (PTC) textile



Winter model



Water repellent



Anti-static properties



Oil-resistant outsole



ESD



ProNose toe reinforcement