

## JALAS® 6498 NATURE

EN ISO 20345:2011, S3 SRC

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SIZE RANGE (EU) 36-47



www.jalas.com



## JALAS® 6498 NATURE

EN ISO 20345:2011, S3 SRC

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SIZE RANGE (EU) 36-47



www.jalas.com



## JALAS® 6498 NATURE

EN ISO 20345:2011, S3 SRC

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SIZE RANGE (EU) 36-47



www.jalas.com



## JALAS® 6498 NATURE

EN ISO 20345:2011, S3 SRC

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SIZE RANGE (EU) 36-47



www.jalas.com



## JALAS® 6498 NATURE

EN ISO 20345:2011, S3 SRC

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SIZE RANGE (EU) 36-47



www.jalas.com



## JALAS® 6498 NATURE

EN ISO 20345:2011, S3 SRC

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SIZE RANGE (EU) 36-47



www.jalas.com



## JALAS® 6498 NATURE

EN ISO 20345:2011, S3 SRC

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SIZE RANGE (EU) 36-47



www.jalas.com



## JALAS® 6498 NATURE

EN ISO 20345:2011, S3 SRC

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SIZE RANGE (EU) 36-47



www.jalas.com



## JALAS® 6498 NATURE

EN ISO 20345:2011, S3 SRC

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SIZE RANGE (EU) 36-47



www.jalas.com



## JALAS® 6498 NATURE

EN ISO 20345:2011, S3 SRC

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SIZE RANGE (EU) 36-47



www.jalas.com

