

## JALAS® 1375

EN ISO 20345:2011, S3 SRB HRO CI

### PROPERTIES

Highest level of protection, excellent grip, perfect fit, extra comfortable, extremely warm, excellent shock absorption

### SPECIFICATION

TYPE OF SHOE Safety footwear, boots/Ankle boots

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Regular

SIZE RANGE (EU) 36-47

PLATFORM Grip

UPPER MATERIAL Full-grain leather

UPPER MATERIAL THICKNESS 1,6-1,8

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester fur

SOLE MATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX2 Winter

INSOLE MATERIAL Textile, aluminium foil, soft EVA, polyester-based conductive thread, Merino wool, double shock absorption zones in Poron® XRD®

FASTENING Laces, zipper

COLOUR Black



1(3)

*The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.*

2018-08-29



SP Technical research institute of Sweden

[www.ejendals.com](http://www.ejendals.com)

## JALAS® 1375

### FEATURES

Heat-resistant outsole, oil-resistant outsole, anti-static properties, padded boot shaft, pull loops, zipper, water repellent, double shock absorption zones

### PREVENTS RISK OF

Toe injuries, nail penetration, antistatic, contact with cold

### PRIMARY ENVIRONMENTS OF USE

Outdoors, environments with risk for outsole penetration, cold environments, harsh environments



CE



Aluminium toecap



Winter model



Nail protection in plasma-treated composite (PTC) textile



Anti-static properties



Heat-resistant outsole



Water repellent



Oil-resistant outsole



Ergothan Shock Absorption System



Zipper

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-29

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

## JALAS® 1375

**COMPLIANCE**  
EN ISO 20345:2011

### COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

S3: S2 + P

WRU: Water-resistant upper

HRO: Heat-resistant outsole compound tested at 300°C

CI: Cold insulation

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRB: Slip-resistance on steel floor with glycerol

BGR 191: Orthopedic footwear adjustment according to German BGR 191. Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Aluminium toecap



Winter model



Nail protection in plasma-treated composite (PTC) textile



Anti-static properties



Heat-resistant outsole



Water repellent



Oil-resistant outsole



Ergo Shock Absorption System



Zipper

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-29

3(3)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com