

JALAS® 1510 ANTISLIP

EN ISO 20345:2011, S1 SRC HRO

PROPERTIES

Excellent grip, perfect fit, extra comfortable, breathable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE Safety footwear, sandals

FITTING Wide

SIZE RANGE (EU) 36-48

COLLECTION Gran Premio

PLATFORM Enduro

UPPER MATERIAL PU-coated leather

UPPER MATERIAL THICKNESS 1,6-1,8

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester, polyamide

SOLE MATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX2 Pro

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron® XRD®

FASTENING Velcro®

COLOUR Black, grey, yellow



SIZE	ART. NO.	EAN NO.	SIZE	ART. NO.	EAN NO.
36	1510-36	6408487442605	48	1510-48	6408487442728
37	1510-37	6408487442612			
38	1510-38	6408487442629			
39	1510-39	6408487442636			
40	1510-40	6408487442643			
41	1510-41	6408487442650			
42	1510-42	6408487442667			
43	1510-43	6408487442674			
44	1510-44	6408487442681			
45	1510-45	6408487442698			
46	1510-46	6408487442704			
47	1510-47	6408487442711			

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS® 1510 ANTISLIP

FEATURES

Wide fit, heat-resistant outsole, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Toe injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Indoors



CE



Aluminium toecap



Heat-resistant outsole



Oil-resistant outsole



Wide fit



Ergothon Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-11-12

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 1510 ANTISLIP

COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

HRO: Heat-resistant outsole compound tested at 300°C

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

BGR 191: Orthopedic footwear adjustment according to German BGR 191. Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Aluminium toecap



Heat-resistant outsole



Oil-resistant outsole



Wide fit



Ergothon Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-11-12

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com