



JALAS® 1884 FIGHTER

EN ISO 20347:2012, 02 SRC HRO CI FO

PROPERTIES

Perfect fit, extra comfortable, good shock absorption

SPECIFICATION

TYPE OF SHOE Occupational footwear, boots/Ankle boots

FITTING Wide

SIZE RANGE (EU) 35-50

PLATFORM Enduro

UPPER MATERIAL Full-grain leather

UPPER MATERIAL THICKNESS 1.8-2.0

PRONOSE MATERIAL PU

LINING MATERIAL Cambrelle®

SOLE MATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX1 Classic

INSOLE MATERIAL Textile, soft EVA, polyester-based
conductive thread, shock absorption zone in Ergothan

FASTENING Laces

COLOUR Black

1(3)

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-07-31



 Finnish Institute of
Occupational Health

SP Technical research institute of Sweden

www.ejendals.com



JALAS® 1884 FIGHTER

FEATURES

ProNose toe reinforcement, wide fit, heat-resistant outsole, oil-resistant outsole, pull loops, water repellent leather, specially designed details, rear shock absorption zone

PRIMARY ENVIRONMENTS OF USE

Outdoors, all-year use

PRIMARY AREAS OF USE

Military work

2(3)

CE



Heat-resistant outsole



Water repellent



Oil-resistant outsole



ProNose toe reinforcement



Wide fit



Shock absorbing

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-07-31

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com



CE



Heat-resistant outsole



Water repellent



Oil-resistant outsole



ProNose toe reinforcement



Wide fit



Shock absorbing

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-07-31

JALAS® 1884 FIGHTER

EU-TYPE EXAMINATION

0403 Finnish Institute of Occupational Health (FIOH)
Topeliuksenkatu 41 b, FI-00250 Helsinki, Finland

COMPLIANCE

EN ISO 20347:2012

COMPLIANCE DESCRIPTION

OB: Footwear with no toe protection against mechanical hazards provided but must provide protection to one or more of the categories P, C, A, E, CI, I, AN, WR or HI

O1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + A + E

O2: O1 + WRU

WRU: Water-resistant upper

HRO: Heat-resistant outsole compound tested at 300°C

CI: Cold insulation

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com