

JALAS® 2102 RICHARD

EN ISO 20347:2012, 02

PROPERTIES

Good grip, perfect fit, extra comfortable, excellent shock absorption, light

SPECIFICATION

TYPE OF SHOE Occupational footwear, loafers

FITTING Regular

SIZE RANGE (EU) 39-47

PLATFORM Comfort

UPPER MATERIAL Full-grain leather

LINING MATERIAL Pigskin, textile

SOLE MATERIAL Plastic shank, PU outsole

INSOLE FX2 Pro

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron® XRD®

FASTENING Elasticated opening

COLOUR Black



The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-29

JALAS® 2102 RICHARD

FEATURES

Oil-resistant outsole, anti-static properties, ventilating insole, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Antistatic

PRIMARY ENVIRONMENTS OF USE

Dry environments, clean environments

PRIMARY AREAS OF USE

Hotel- and restaurant work, service work, office work

PRIMARY INDUSTRIES OF USE

HoReCa, service



Oil-resistant outsole



Ergo-Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-29

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 2102 RICHARD

COMPLIANCE
EN ISO 20347:2012

COMPLIANCE DESCRIPTION

O2: O1 + WRU

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm



CE



Oil-resistant outsole



Ergothon Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-29

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com