

## JALAS® 2900 JACK

EN ISO 20345:2011, SB A E FO SRC

### PROPERTIES

Excellent grip, perfect fit, extra comfortable, excellent shock absorption

### SPECIFICATION

TYPE OF SHOE Safety footwear, clogs

FITTING Regular

SIZE RANGE (EU) 34-47

PLATFORM Gram

UPPER MATERIAL Microfiber

TOECAP MATERIAL Steel

LINING MATERIAL Polyester

SOLE MATERIAL Plastic shank, PU outsole

INSOLE FX2 Pro

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron® XRD®

FASTENING Velcro®

COLOUR Black

ANTIBACTERIAL/BIOCIDAL TREATMENT Pyrithione zinc (CAS number 13463-41-7)



| SIZE | ART. NO. | EAN NO.       | SIZE | ART. NO. | EAN NO.       |
|------|----------|---------------|------|----------|---------------|
| 34   | 2900-34  | 6408487387753 | 46   | 2900-46  | 6408487387876 |
| 35   | 2900-35  | 6408487387760 | 47   | 2900-47  | 6408487387883 |
| 36   | 2900-36  | 6408487387777 |      |          |               |
| 37   | 2900-37  | 6408487387784 |      |          |               |
| 38   | 2900-38  | 6408487387791 |      |          |               |
| 39   | 2900-39  | 6408487387807 |      |          |               |
| 40   | 2900-40  | 6408487387814 |      |          |               |
| 41   | 2900-41  | 6408487387821 |      |          |               |
| 42   | 2900-42  | 6408487387838 |      |          |               |
| 43   | 2900-43  | 6408487387845 |      |          |               |
| 44   | 2900-44  | 6408487387852 |      |          |               |
| 45   | 2900-45  | 6408487387869 |      |          |               |

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## JALAS® 2900 JACK

### FEATURES

Oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

### PREVENTS RISK OF

Toe injuries, antistatic

### PRIMARY ENVIRONMENTS OF USE

Indoors

### PRIMARY AREAS OF USE

Foodstuff handling, food handling, kitchen work

### PRIMARY INDUSTRIES OF USE

Food processing



Steel toecap



Oil-resistant outsole



Ergothon Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-05-20

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

## JALAS® 2900 JACK

**COMPLIANCE**  
EN ISO 20345:2011

### COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

BGR 191: Orthopedic footwear adjustment according to German BGR 191. Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Steel toecap



Oil-resistant outsole



Ergothon Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-05-20

3(3)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com