

JALAS® 2982 RONJA

EN ISO 20347:2012, OB A E SRC FO

PROPERTIES

Excellent grip, perfect fit, comfortable, breathable, excellent shock absorption, light

SPECIFICATION

TYPE OF SHOE Occupational footwear, clogs

FITTING Regular

SIZE RANGE (EU) 34-42

COLLECTION Gram à la Sara

PLATFORM Gram

UPPER MATERIAL Microfiber

LINING MATERIAL Polyester, polyamide

SOLE MATERIAL Plastic shank, PU outsole

INSOLE FX2 Pro

INSOLE MATERIAL Textile, soft EVA, double shock absorption zones in Poron® XRD®

FASTENING Velcro®

COLOUR White, black



SIZE	ART. NO.	EAN NO.
34	2982-34	6408487434952
35	2982-35	6408487434969
36	2982-36	6408487434976
37	2982-37	6408487434983
38	2982-38	6408487434990
39	2982-39	6408487435003
40	2982-40	6408487435010
41	2982-41	6408487435027
42	2982-42	6408487435034

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS® 2982 RONJA

FEATURES

Low weight, oil-resistant outsole, anti-static properties, adjustable heel strap, ESD, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Antistatic, slipping

PRIMARY ENVIRONMENTS OF USE

Indoors, office environments, dry environments, clean environments

PRIMARY AREAS OF USE

Cleaning, kitchen work, hotel- and restaurant work, healthcare, care work, service work, office work, shop work

PRIMARY INDUSTRIES OF USE

HoReCa, service



Oil-resistant outsole



Ergothon Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-04-10

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 2982 RONJA

COMPLIANCE
EN ISO 20347:2012

COMPLIANCE DESCRIPTION

OB: Footwear with no toe protection against mechanical hazards provided but must provide protection to one or more of the categories P, C, A, E, CI, I, AN, WR or HI

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRC: SRA + SRB

ESD: Electro Static Discharge

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm



CE



Oil-resistant outsole



Ergothon Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-04-10

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com