

JALAS® 3000 ZENIT

EN ISO 20345:2011, S1 SRC

PROPERTIES

Highest level of protection, excellent grip, perfect fit, extra comfortable, very breathable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE Safety footwear, sandals

FITTING Regular

SIZE RANGE (EU) 36-47

COLLECTION Zenit

PLATFORM Zenit

UPPER MATERIAL PU-coated leather, split leather

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyamide, polyester

SOLE MATERIAL PU midsole, plastic shank, RPU outsole

BIND SOLE MATERIAL SBS

INSOLE FX2 Supreme

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, Merino wool, double shock absorption zones in Poron® XRD®

FASTENING Velcro®

COLOUR Black, grey, red



ZENIT
COLLECTION



reddot design award
winner 2012

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-29



Finnish Institute of
Occupational Health

SP Technical research institute of Sweden

www.ejendals.com

JALAS® 3000 ZENIT

FEATURES

Breathable membrane, patented by Geox, perforated, oil-resistant outsole, anti-static properties, padded shaft edge in memory foam, ventilating insole, stabilizer, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Toe injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Indoors, dry environments



CE



Aluminium toecap



Oil-resistant outsole



Ergothon Shock Absorption System



Stabilizer



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-29

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 3000 ZENIT

COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

BGR 191: Orthopedic footwear adjustment according to German BGR 191. Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Aluminium toecap



Oil-resistant outsole



Ergothon Shock Absorption System



Stabilizer



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-29

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com