

JALAS® 3308 DRYLOCK

EN ISO 20345:2011, S3 HRO WR SRB

PROPERTIES

Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE Safety footwear, low shoes

NAIL PROTECTION MATERIAL Steel

FITTING Regular

SIZE RANGE (EU) 36-47

COLLECTION Drylock

PLATFORM Grip

UPPER MATERIAL Full-grain leather, Cordura®

UPPER MATERIAL THICKNESS 1.6-1.8

PRONOSE MATERIAL PU

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester, polyamide, Drylock membrane

SOLE MATERIAL PU midsole, rubber outsole

INSOLE FX2 Supreme

INSOLE MATERIAL Textile, soft EVA, Merino wool, double shock absorption zones in Poron® XRD®

FASTENING Laces

COLOUR Black, grey, red



DRY+LOCK

SIZE	ART. NO.	EAN NO.
36	3308-36	6408487427824
37	3308-37	6408487427831
38	3308-38	6408487427848
39	3308-39	6408487427855
40	3308-40	6408487427862
41	3308-41	6408487427879
42	3308-42	6408487427886
43	3308-43	6408487427893
44	3308-44	6408487427909
45	3308-45	6408487427916
46	3308-46	6408487427923
47	3308-47	6408487427930

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS® 3308 DRYLOCK

FEATURES

Waterproof Drylock-membrane, ProNose toe reinforcement, heat-resistant outsole, oil-resistant outsole, anti-static properties, bellows tongue, polstered shaft edge, ventilating insole, waterproof, reflector, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic, wet feet

PRIMARY ENVIRONMENTS OF USE

Outdoors, environments with risk for outsole penetration, wet environments, harsh environments



CE



Aluminium toecap



Anti-static properties



Nail protection in steel



ESD



Heat-resistant outsole



Waterproof



Oil-resistant outsole



ProNose toe reinforcement



Ergothon Shock Absorption System

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-11-15

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 3308 DRYLOCK

COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

S3: S2 + P

WR: Water-resistant footwear

WRU: Water-resistant upper

P: Penetration-resistant outsole

HRO: Heat-resistant outsole compound tested at 300°C

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRB: Slip-resistance on steel floor with glycerol

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

BGR 191: Orthopedic footwear adjustment according to German BGR 191. Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Aluminium toecap



Anti-static properties



Nail protection in steel



ESD



Heat-resistant outsole



Waterproof



Oil-resistant outsole



ProNose toe reinforcement



Ergothon Shock Absorption System

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-11-15

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com