

JALAS® 3312 DRYLOCK

EN ISO 20347:2012, 02 SRB WR HRO FO

PROPERTIES

Excellent grip, perfect fit, extra comfortable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE Occupational footwear, boots/Ankle boots

FITTING Regular

SIZE RANGE (EU) 36-47

COLLECTION Drylock

PLATFORM Grip

UPPER MATERIAL Full-grain leather, Cordura®

LINING MATERIAL Polyester, polyamide, Drylock membrane

SOLE MATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX2 Supreme

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, Merino wool, double shock absorption zones in Poron® XRD®

FASTENING Laces

COLOUR Black, grey, red



DRY+LOCK

SIZE	ART. NO.	EAN NO.
36	3312-36	6408487435133
37	3312-37	6408487435140
38	3312-38	6408487435157
39	3312-39	6408487435164
40	3312-40	6408487435171
41	3312-41	6408487435188
42	3312-42	6408487435195
43	3312-43	6408487435201
44	3312-44	6408487435218
45	3312-45	6408487435225
46	3312-46	6408487435232
47	3312-47	6408487435249

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS® 3312 DRYLOCK

FEATURES

Waterproof Drylock-membrane, heat-resistant outsole, oil-resistant outsole, anti-static properties, bellows tongue, padded boot shaft, ventilating insole, waterproof, reflector, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Antistatic, wet feet

PRIMARY ENVIRONMENTS OF USE

Outdoors, all-year use, wet environments



CE



Heat-resistant outsole



Waterproof



Oil-resistant outsole



Ergothon Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-11-15

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 3312 DRYLOCK

COMPLIANCE
EN ISO 20347:2012

COMPLIANCE DESCRIPTION

O1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + A + E

O2: O1 + WRU

WR: Water-resistant footwear

WRU: Water-resistant upper

HRO: Heat-resistant outsole compound tested at 300°C

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRB: Slip-resistance on steel floor with glycerol

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

BGR 191: Orthopedic footwear adjustment according to German BGR 191. Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Heat-resistant outsole



Waterproof



Oil-resistant outsole



Ergothon Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-11-15

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com