

JALAS® 3325 DRYLOCK

EN ISO 20345:2011, S3 HRO WR SRB

PROPERTIES

Highest level of protection, excellent grip, perfect fit, extra comfortable, extremely warm, excellent shock absorption

SPECIFICATION

TYPE OF SHOE Safety footwear, boots/Ankle boots

NAIL PROTECTION MATERIAL Steel

FITTING Regular

SIZE RANGE (EU) 36-47

COLLECTION Drylock

PLATFORM Grip

UPPER MATERIAL Full-grain leather

TOECAP MATERIAL Aluminium

LINING MATERIAL ThermoCloud - thermal insulation, polyester, Drylock membrane

SOLE MATERIAL PU midsole, rubber outsole

INSOLE FX2 Winter

INSOLE MATERIAL Textile, aluminium foil, soft EVA, polyester-based conductive thread, Merino wool, double shock absorption zones in Poron® XRD®

FASTENING Laces, zipper

COLOUR Black, grey, red



DRY+LOCK

SIZE	ART. NO.	EAN NO.
36	3325-36	6408487500695
37	3325-37	6408487500701
38	3325-38	6408487500718
39	3325-39	6408487500725
40	3325-40	6408487500732
41	3325-41	6408487500749
42	3325-42	6408487500756
43	3325-43	6408487500763
44	3325-44	6408487500770
45	3325-45	6408487500787
46	3325-46	6408487500794
47	3325-47	6408487500800

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS® 3325 DRYLOCK

FEATURES

Waterproof Drylock-membrane, heat-resistant outsole, oil-resistant outsole, anti-static properties, bellows tongue, padded boot shaft, pull loops, snow lock, zipper, waterproof, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic, contact with cold

PRIMARY ENVIRONMENTS OF USE

Outdoors, environments with risk for outsole penetration, wet environments, harsh environments



CE



Aluminium toecap



Winter model



Nail protection in steel



Anti-static properties



Heat-resistant outsole



ESD



Waterproof



Oil-resistant outsole



Ergothon Shock Absorption System



Zipper

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-11-15

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 3325 DRYLOCK

COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

S3: S2 + P

WR: Water-resistant footwear

P: Penetration-resistant outsole

HRO: Heat-resistant outsole compound tested at 300°C

A: Electrical resistance (between 0.1-1000 Mega Ohms

E: Energy absorption in the heel area (tested at 20 Joules)

SRB: Slip-resistance on steel floor with glycerol

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

BGR 191: Orthopedic footwear adjustment according to German BGR 191. Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Aluminium toecap



Winter model



Nail protection in steel



Anti-static properties



Heat-resistant outsole



ESD



Waterproof



Oil-resistant outsole



Ergo Shock Absorption System



Zipper

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-11-15

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com