

JALAS® 3700R RESPIRO

EN ISO 20345:2011, S2 SRB

PROPERTIES

Good grip, perfect fit, extra comfortable, very breathable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE Safety footwear, low shoes

FITTING Regular

SIZE RANGE (EU) 36-47

COLLECTION Respiro

PLATFORM Stabilizator

UPPER MATERIAL PU-coated leather, nubuck leather, textile

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester, polyamide

SOLE MATERIAL PU midsole, plastic shank, TPU outsole

INSOLE FX2 Supreme

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, Merino wool, double shock absorption zones in Poron® XRD®

FASTENING Laces

COLOUR Black, red, blue



RESPIRO

SIZE	ART. NO.	EAN NO.
36	3700R-36	6408487504631
37	3700R-37	6408487504648
38	3700R-38	6408487504655
39	3700R-39	6408487504662
40	3700R-40	6408487504679
41	3700R-41	6408487504686
42	3700R-42	6408487504693
43	3700R-43	6408487504709
44	3700R-44	6408487504716
45	3700R-45	6408487504723
46	3700R-46	6408487504730
47	3700R-47	6408487504747

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



JALAS® 3700R RESPIRO

FEATURES

Ultra-high air permeability, three-layer laminate, 'provided by IQTEX based on patented technologies', perforated, oil-resistant outsole, anti-static properties, polstered shaft edge, stabilizer, water repellent, perforated front section, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Toe injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Indoors, dry environments, clean environments

2(3)



Aluminium toecap



Water repellent



Oil-resistant outsole



Ergothon Shock Absorption System



Stabilizer



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-11-15

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 3700R RESPIRO

COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

WRU: Water-resistant upper

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRB: Slip-resistance on steel floor with glycerol

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

BGR 191: Orthopedic footwear adjustment according to German BGR 191. Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Aluminium toecap



Water repellent



Oil-resistant outsole



Ergothon Shock Absorption System



Stabilizer



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-11-15

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com