

JALAS® 5352 SPOC EASYROLL

EN ISO 20347:2012, O2 A E FO SRC

PROPERTIES

High level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption, light

SPECIFICATION

TYPE OF SHOE Occupational footwear, low shoes

FITTING Regular

SIZE RANGE (EU) 35-48

COLLECTION Sp0c

PLATFORM Active

UPPER MATERIAL Full-grain leather

LINING MATERIAL Polyester

SOLE MATERIAL EVA, rubber outsole

INSOLE FX2 PRO Sp0c insole

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron® XRD®

FASTENING Boa®

COLOUR Black

ANTIBACTERIAL/BIOCIDAL TREATMENT Pyrithione zinc (CAS number 13463-41-7)



BOA®

SIZE	ART. NO.	EAN NO.	SIZE	ART. NO.	EAN NO.
35	5352-35	6408487508608	47	5352-47	6408487508639
36	5352-36	6408487508745	48	5352-48	6408487508622
37	5352-37	6408487508738			
38	5352-38	6408487508721			
39	5352-39	6408487508714			
40	5352-40	6408487508707			
41	5352-41	6408487508691			
42	5352-42	6408487508684			
43	5352-43	6408487508677			
44	5352-44	6408487508660			
45	5352-45	6408487508653			
46	5352-46	6408487508646			

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS® 5352 SPOC EASYROLL

FEATURES

Low weight, oil-resistant outsole, anti-static properties, Boa® closure system, ESD, water repellent leather, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Prevents risk of: sprain injuries, antistatic, slipping, strain injuries

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, office environments, all-year use, slippery environments, dry environments, clean environments

PRIMARY AREAS OF USE

Security- and police work, cleaning, hotel- and restaurant work, healthcare, care work, service work, office work, shop work

PRIMARY INDUSTRIES OF USE

HoReCa, service, retail



Water repellent



Oil-resistant outsole



Ergothon Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-05-20

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 5352 SPOC EASYROLL

COMPLIANCE
EN ISO 20347:2012

COMPLIANCE DESCRIPTION

O2: O1 + WRU

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm



CE



Water repellent



Oil-resistant outsole



Ergothon Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-05-20

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com