

## JALAS® 9615 FLOW

EN ISO 20345:2011, S3 SRC HRO

### PROPERTIES

Perfect fit, extra comfortable, excellent shock absorption, light

### SPECIFICATION

TYPE OF SHOE Safety footwear, low shoes

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Narrow/Regular

SIZE RANGE (EU) 34-43

COLLECTION Flow

PLATFORM Performance

UPPER MATERIAL Microfiber, Cordura®

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester

SOLE MATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX3 Exalter2

INSOLE MATERIAL Textile, soft EVA, rigid EVA, polyester-based conductive thread, neo foam, double shock absorption zones in Poron® XRD®

FASTENING Laces

COLOUR Black, turquoise

ANTIBACTERIAL/BIOCIDAL TREATMENT Pyrrhione zinc (CAS number 13463-41-7)



**FLOW**



SIZE	ART. NO.	EAN NO.
34	9615-34	6408487505584
35	9615-35	6408487505591
36	9615-36	6408487505607
37	9615-37	6408487505614
38	9615-38	6408487505621
39	9615-39	6408487505638
40	9615-40	6408487505645
41	9615-41	6408487505652
42	9615-42	6408487505669
43	9615-43	6408487505676

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-05-17

1(3)



Finnish Institute of Occupational Health

SP Technical research institute of Sweden

www.ejendals.com

## JALAS® 9615 FLOW

### FEATURES

Heat-resistant outsole, oil-resistant outsole, anti-static properties, ventilating insole, extra shoelaces, stabilizer, water repellent, anatomically designed, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

### PREVENTS RISK OF

Toe injuries, nail penetration, sprain injuries, antistatic

### PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, environments with risk for outsole penetration



Aluminium toecap



Anti-static properties



Nail protection in plasma-treated composite (PTC) textile



ESD



Heat-resistant outsole



Water repellent



Oil-resistant outsole



Ergothon Shock Absorption System



Stabilizer

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-05-17

2(3)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

## JALAS® 9615 FLOW

**COMPLIANCE**  
EN ISO 20345:2011

### COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

S3: S2 + P

WRU: Water-resistant upper

P: Penetration-resistant outsole

HRO: Heat-resistant outsole compound tested at 300°C

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm



CE



Aluminium toecap



Anti-static properties



Nail protection in plasma-treated composite (PTC) textile



ESD



Heat-resistant outsole



Water repellent



Oil-resistant outsole



Ergothon Shock Absorption System



Stabilizer

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-05-17

3(3)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com