



**jalas**®

## JALAS® 3118 LIGHT GRIP

EN ISO 20345:2011, S3, SRB, HRO

**PROPERTIES** Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

**PRIMARY ENVIRONMENTS OF USE** Outdoors, environments with risk for outsole penetration

**FEATURES** ProNose toe reinforcement, heat-resistant outsole, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

**UPPER MATERIAL** Split leather, Textile

**SOLE MATERIAL** PU midsole, plastic shank, rubber outsole

**INSOLE** FX2 Pro

**FITTING** Regular

**SIZE RANGE (EU)** 36-47

CE



Aluminium toecap



ProNose toe reinforcement



Nail protection in plasma-treated composite (PTC) textile



Ergo Shock Absorption System



Heat-resistant outsole



Anti-static properties



Water repellent



ESD



Oil-resistant outsole



**jalas**®

## JALAS® 3118 LIGHT GRIP

EN ISO 20345:2011, S3, SRB, HRO

**PROPERTIES** Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

**PRIMARY ENVIRONMENTS OF USE** Outdoors, environments with risk for outsole penetration

**FEATURES** ProNose toe reinforcement, heat-resistant outsole, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

**UPPER MATERIAL** Split leather, Textile

**SOLE MATERIAL** PU midsole, plastic shank, rubber outsole

**INSOLE** FX2 Pro

**FITTING** Regular

**SIZE RANGE (EU)** 36-47

CE



Aluminium toecap



ProNose toe reinforcement



Nail protection in plasma-treated composite (PTC) textile



Ergo Shock Absorption System



Heat-resistant outsole



Anti-static properties



Water repellent



ESD



Oil-resistant outsole