TEGERA®

TEGERA® 98

Cut sleeve, Dyneema®, nylon, 13 gg, cut resistance level B, Cat. II, high visibility colour

TEGERA® 98

Learn more

Cut sleeve, Dyneema®, nylon, 13 gg, cut resistance level B, Cat. II, high visibility colour

CHARACTERISTICS

- Good fit
- Light
- Flexible
- Durable
- Comfortable
- Breathable
- High level of protection

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

cut injuries, abrasion injuries, grazes, scratches, lacerations

PRIMARY ENVIRONMENTS OF USE

cut risk environments, harsh environments

PRIMARY AREAS OF USE

fine assembly, assembly, inspection work, machine operating, building and construction, carpentry, installation work, sheet-metal work, construction, warehouse work, glass industry work, wood industry work

PRIMARY INDUSTRIES OF USE

mining, pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, mro, automotive, transportation, utilities, building and construction

SPECIFICATION

COLOUR Green
PIECES PER: BUNDLE/CARTON 10/100

CE

EAC

EN 420:2003 +A1:2009

EN 388:2016

Information/UIS

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.