

TEGERA® PRO 9125

Ergonomic, synthetic glove with Microthan+® and reinforced safety features. Long lasting thanks to the durable Microthan+ synthetic leather.

TYPE All-round work gloves, Assembly gloves, Heavy duty gloves
CHARACTERISTICS good fingertip sensitivity, flexible, excellent grip, very durable, perfect fit, extra comfortable
SIZES 7, 8, 9, 10, 11, 12, 13

CE Cat. II Short model (EN 420) EN 388:2016 2131X EN 420:2003 +A1:2009



EJENDALS.COM

Microthan+

JALAS® EXALTER 9975

This mid-cut safety shoe has the features you need for most work situations, such as textile nail protection, toecap in aluminum and high-grip Vibram Nitrile rubber outsole.

CHARACTERISTICS highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption
SIZE RANGE 34-47

CE EN ISO 20345:2011 S3, SRC, HRO



EJENDALS.COM



JALAS® ZENIT EVO 7158

A comfortable safety shoe with colorful sport-inspired design, BOA® Fit System and high-quality protection.

CHARACTERISTICS excellent grip, perfect fit, extra comfortable, very breathable, excellent shock absorption, extremely light
SIZE RANGE 35-48

CE EN ISO 20345:2011 S1, P, SRC



EJENDALS.COM



TEGERA® INFINITY 8801

Dexterous work glove, 15 gg knitted with super soft nitrile foam that provides excellent grip on dry surfaces. Breathable materials for all day comfort.

TYPE Heat protection gloves, Precision work gloves
CHARACTERISTICS high level of protection, extremely good fingertip sensitivity, extra flexible, durable, good grip, extra comfortable
SIZES 5, 6, 7, 8, 9, 10, 11

CE Cat. II EN 407:2004 XiXXXX EN 388:2016 4121X EN 420:2003 +A1:2009



EJENDALS.COM

JALAS® NEUTRALIZER 8709H HIGH ARCH

Insole for high arches that makes your Jalas shoes even more comfortable and safe. Double shock absorption zones in Poron® XRD® reduces the risk of injury and increase comfort.

CHARACTERISTICS perfect fit, extra comfortable, breathable, excellent shock absorption
SIZES 34-35, 36-37, 38-39, 40-41, 42-43, 44-45, 46-47, 48-50



EJENDALS.COM

